

## Features



Outdoor digital and silk screen printing media for signage display, vehicle graphics, airport and subway graphics application. 12 months under ordinary condition at temperature of 22°C and relative humidity of 50-55%

## Technical Data Sheet

Item Code		SAMVXK08120E
PVC Face Film	Type	Calendered Monomeric soft PVC film
	Thickness (mm)	0.08±0.01
	Color	White
	60 ° Reflection Angle	88°±5°
Glue	Type	Transparent Permanent
	Thickness (um)	25±3
	180° Peeling Force	≥8N / 25MM
	Holding Power	≥ 24 Hours
Liner Paper	Type	Single side polycoated wood pulp paper
	Weight (gsm)	120±6

Information contained in this document is based on our general experience and is given in good faith. But we are unable to accept responsibility in respect to factors which are outside our knowledge or control.

## Ink Printability

SOLVENT	ECO-SOLVENT	UV	LATEX	SCREEN PRINTING
■	■	■	■	■



Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District,  
Haining, Zhejiang, China  
Tel: +86-573-80776996 Fax: +86-573-80776998  
Mob/Skype/Wechat/WhatsApp: +86-15858322153  
<mailto:contact@hncomax.com> <https://www.hncomax.com>

